


Series SG5

Contractor Gage

Large, Easy-to-Read Dial



The Series SG5 Contractor Gages are ideally manufactured for contractors because of their large dial and compact design. Since the gages are lightweight and slim, they are easy to transport. The large $4.5\,^{\prime\prime}$ scale makes them simple to read. The Series SG5 gages possess psi scales with 1% full-scale accuracy. The gages are made with a stainless steel housing and brass wetted parts. Units can withstand temperatures of 4 to $140\,^{\circ}$ F (20 to $60\,^{\circ}$ C). These qualities make the SG5 series perfect for contractors and industrial applications. A wide offering of ranges are available from full vacuum to $300\,^{\circ}$ psi.

Model	Ranges
SG5-G0122N	30" Hg to 0
SG5-G0322N	0 to 30 PSI
SG5-G0422N	0 to 60 PSI
SG5-G0522N	0 to 100 PSI
SG5-G0622N	0 to 160 PSI
SG5-G0722N	0 to 200 PSI
SG5-G0822N	0 to 300 PSI

SPECIFICATIONS:

Service: Compatible gases and liquids.

Wetted Materials: Brass connection, bronze tube.

Housing: 304 SS. Lens: Plastic. Accuracy: ±1% FS.

Pressure Limits: Full scale range.

Temperature Limits: -4 to 140°F (-20 to 60°C).

Size: 4.5" (115 mm).

Process Connections: 1/4" male NPT.

Weight: 10.4 oz (295 g).

OPTION

For NIST traceable calibration certificate, use order code NISTCAL-PG1.