INDUSTRIAL AND PROCESS APPLICATIONS

PTF601 Sanitary diaphragm pressure gauges are designed for use in Pharmaceutical, Biotechnology, Food, Beverages and Dairy applications. They are constructed with hygienic Tri-clamp sealed connections for measuring pressure in sanitary applications and are free of voids and cavities to allow no areas for bacterial growth.

- · All Stainless steel construction
- · Excellent load cycle stability and shock resistance
- · 4-20mA, 2-wire output signal
- Ranges from (-1) to 40 bar
- · DIN 43650 plug-in connectors
- · Cooling tower for high temperature application optional

APPLICATIONS

- · Food & Beverage
- Pharmaceutical
- Cosmetic

STANDARD FEATURES

Signal output : 4-20 mA, 2-wire
Supply voltage : 10-30 VDC

Electrical connection: DIN 43650 with plug connector
Process connection: 1", 1.5" or 2" Triclover connection

PERFORMANCE @25 °C (77 °F)

 Accuracy (non-linearity, hysteresis & non-repeatability): <±1% span

• Stability (1 year): ±1% span

Over range protection : 2X Rated pressure

· Burst pressure: 4X Rated pressure

ELECTRICAL DATA

Output: 4-20 mA, 2-wireExcitation: 10 - 30 VDC

Output impedance : >100K Ohms
Current consumption : 20mA, typical

TEMPERATURE


- Compensated Range : -20 to 85 $^{\circ}\text{C}$

Operating : -40 to 125 °CStorage : -40 to 125 °C

OTHER

Shock: 50G, 11 msec, 1/2 sineVibration: 20G peak, 20 to 2000Hz

HOW TO ORDER





STANDARD PRESSURE & COMPOUND RANGES

PRESSURE RANGES		COMPOUND
		RANGES
0 to 1 Barg	0 to 20 Barg	-1 to 3 Barg
0 to 2 Barg	0 to 25 Barg	-1 to 6 Barg
0 to 3.5 Barg	0 to 30 Barg	-1 to 25 Barg
0 to 4 Barg	0 to 40 Barg	-1 to 0 Barg
0 to 6 Barg		
0 to 7 Barg		
0 to 10 Barg		
0 to 16 Barg		
1		I

Other equivalent units of pressure & vaccum are available on request

ACCESSORIES

CODE	SANITARY GASKETS	
GF	Silicone, FDA Approved	
GP	Silicone, FDA Approved & Phthalate Free	

CODE	TRICLOVER FERRULE
TC25x21.5	1" Tri-clover Ferrule
TC40x21.5	1.5" Tri-clover Ferrule
TC50x21.5	2" Tri-clover Ferrule

CODE	CLAMP
TC25	1" Clamp
TC40	1.5" Clamp
TC50	2" Clamp

radix®

DAT#270R1